PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau





INTERNATIONAL APPLICATION PUBLISH	HED	NDER THE PATENT COOPERATION TREATY (PCT)
(51) International Patent Classification ⁶ : A61L 27/00, A61F 2/12	A1	(11) International Publication Number: WO 95/25549 (43) International Publication Date: 28 September 1995 (28.09.95)
 (21) International Application Number: PCT/USS (22) International Filing Date: 4 November 1994 (6) (30) Priority Data: 08/217,206 23 March 1994 (23.03.94) 08/259,474 14 June 1994 (14.06.94) (71) Applicant: LIPOMATRIX INCORPORATED [VG/U Embarcadero Road, Palo Alto, CA 94303 (US). (72) Inventors: KNAPP, Terry, R.; 9A, rue de Saint-I CH-2000 Neuchâtel (CH). ANDREWS, Winston, El Capitan Drive, Danville, CA 94526 (US). DI Gloria, R.; 1764 Camargo Drive, San Jose, CA 951 (74) Agent: HAFERKAMP, Richard, E.; Rogers, Howell kamp, Suite 1400, 7733 Forsyth Boulevard, St. Lo 63105 (US). 	04.11.9 US]; 18 Nichol, A.; 5 UMLA 132 (U	(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LT, LU, LV, MD, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: SYNTHETIC TRIGLYCERIDE FILLER MATERIAL FOR SURGICALLY IMPLANTED PROSTHESES

(57) Abstract

A filler material for a surgically implantable prosthesis comprised of a synthetic triglyceride having a viscosity substantially greater than that of naturally occurring triglycerides is provided. The triglyceride composition is formed of saturated alkyl chains to reduce or limit the potential for oxidation of the alkyl chains to form peroxide groups which adversely affect the biocompatibility of the filler material and the implant. Preferably, the filler material has a viscosity substantially the equivalent of a normal human breast. The synthetic triglyceride filler material may also have a lower viscosity which is a liquid at room temperature for use in inflatable devices. Prostheses containing filler material having the desired viscosity and antioxidation characteristics are also provided as well as a method for preparing the filler material.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

ΑT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
	Barbados	GN	Guinea	NE	Niger
BB		GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin			PT	Portugal
BR	Brazil	JP	Japan	RO	Romania
BY	Belarus	KE	Kenya	RU	Russian Federation
CA	Canada	KG	Kyrgystan	SD	Sudan
CF	Central African Republic	KP	Democratic People's Republic	SE	Sweden
CG	Congo		of Korea		
СН	Switzerland	KR	Republic of Korea	SI	Slovenia
CI	Côte d'Ivoire	KZ	Kazakhstan	SK	Slovakia
CM	Cameroon	LI	Liechtenstein	SN	Senegal
CN	China	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
CZ	Czech Republic	LV	Latvia	TJ	Tajikistan
	-	MC	Monaco	TT	Trinidad and Tobago
DE	Germany	MD	Republic of Moldova	UA.	Ukraine
DK	Denmark	MG	Madagascar	US	United States of America
ES	Spain	ML	Mali	UZ	Uzbekistan
FI	Finland			VN	Viet Nam
FR	France	MN	Mongolia	***	1 200 1 1000
GA	Gabon				

SYNTHETIC TRIGLYCERIDE FILLER MATERIAL FOR SURGICALLY IMPLANTED PROSTHESES

Field of the Invention

This invention generally relates to surgical implants or prostheses, and more particularly to a filler material for implants comprising a flexible shell enclosing a filler material and implants containing the filler material.

Background of the Invention

Surgical implants requiring a filler material, such as breast implants, penile implants, or musculature implants, have conventionally used a silicone gel or a saline solution as the filler material. One of the primary concerns in the design of an implant is to provide a tactile response that is comparable to the tactile response of normal human tissue. Silicone has been the filler material of choice primarily because silicone filled implants provided an adequate tactile response, but the very nature of the silicone filler material also

2

limits the desirability of its tactile properties. Silicone filled implants typically comprise about 10-20% cross-linked silicone which forms an interconnected "sponge" in the implant with the remainder of the filler 5 material being low molecular weight silicone oil. Because of this "sponge", silicone filled implants are stiffer than human tissue, such as breast tissue, and do not provide the same feel as human tissue. Moreover, adverse medical consequences have recently become associ-10 ated with the use of silicone gel filled implants because it has been discovered that the silicone oil can migrate through the implant shell and the silicone oil is not biocompatible with other human tissues. Therefore, the use of silicone based filler materials has been discon-15 tinued in the industry. Saline filled implants have not exhibited any adverse medical consequences when used as a filler material in an implant, but saline is not considered a preferred filler material because of the relatively low viscosity (~lcp) of such a solution which renders 20 undesirable its tactile properties.

In U.S. Patent No. 4,995,882 issued to Destouet et al., the rights to which are owned by the assignee herein, naturally occurring, vegetable derived triglyceride oils were proposed for use as a filler material for a 25 breast implant. This represented a dramatic break from the teaching of the prior art and is a good and valuable invention. One of the stated reasons for using a triglyceride oil composition was to take advantage of the radiolucent characteristics thereof so that a useful 30 mammogram could be performed of an implanted breast. Although this radiolucency characteristic is important for mammograms, the naturally occurring triglyceride oil compositions disclosed by Destouet et al., such as peanut oil and sunflower seed oil, have a relatively low viscos-35 ity (~30cps) and as such do not completely provide the desired tactile response of a normal breast. Further-

3

more, naturally occurring triglyceride oils typically contain unsaturated and/or polyunsaturated alkyl groups which are susceptible to oxidation. It is known that polyunsaturated fatty acid side chains of triglycerides 5 will react with molecular oxygen to create unstable reduction products such as superoxide and hydrogen perox-This is known as lipid peroxidation or rancidifica-The reaction forms peroxy lipid radicals and evention. tually results in the formation of shorter chain com-10 pounds such as malondialdehyde, ethane, pentane and 4hydroxyalkenals, free fatty acids, and the unstable superoxide and peroxide moieties. The free radicals produced as a result of lipid peroxidation are capable of harming cells and cellular components as well as molecular struc-15 tures essential to the organism. Because of the hydrophobic nature of lipid radicals, it is believed that membrane associated molecules would be most at risk, but other molecular species such as non-oxidized lipids, carbohydrates, lipoproteins and nucleic acids could be Thus, it is believed that the oxidation of unsaturated alkyl chains on a triglyceride may reduce over time the biocompatability of naturally occurring triglycerides in an implant.

There is, therefore, room for improvement with a 25 filler material which retains the radiolucent characteristics of a naturally occurring triglyceride oil while also having an improved viscosity and biocompatability, and implants containing such a filler material.

Summary of the Invention

30

The present invention is directed to a filler material for a surgically implantable prothesis that exhibits the radiolucent characteristics of naturally occurring triglycerides but which also has a greater viscosity and which provides a tactile response substan-35 tially the equivalent of the tactile response of normal

PCT/US94/12394 WO 95/25549

human tissue, such as breast tissue. According to the invention, a synthetic triglyceride composition containing triglycerides having saturated alkyl chains of between 4 and 26 carbons in length in proportions such that 5 the triglyceride composition has a viscosity substantially greater than naturally occurring triglyceride oils is provided. Preferably, the filler material provides a tactile response substantially the equivalent of the tactile response of normal human tissue, and has a vis-10 cosity of about 10,000cps at a temperature of between about 32°C and about 40°C. Its viscosity can be compared to that of a viscous paste over the extremes of physiologic temperature, i.e. 32°C to 40°C. This is achieved by providing a triglyceride composition having alkyl 15 chains of varying lengths in selected proportions to provide this increased viscosity characteristic.

In another aspect of the invention, the filler material is prepared in a manner which reduces its susceptibility to autoxidation to enhance its 20 biocompatibility. This is achieved by utilizing triglycerides that have substantially all saturated alkyl groups or by the inclusion of antioxidants with the filler material.

In still another aspect of the invention, a surgi-25 cally implantable prosthesis containing a filler material that can be provided in a range of viscosities, and a method for preparing such a filler material, is provided. This enables the provision and production of an implant having a pre-selected viscosity or tactile response.

30

In yet another aspect of the invention, a synthetic triglyceride composition containing triglycerides having fully saturated fatty acid (alkyl) side chains in proportions providing a composition that is a liquid at room temperature (~23°C) is provided. This filler mate-35 rial has a viscosity similar to that of naturally occurring triglyceride oils, but is fully saturated to limit

5

the possibility of oxidation and can be readily injected via a small diameter delivery tube into an already implanted device.

The present invention is further directed to
5 surgically implantable prostheses containing this filler
material within the sealed shell of the prosthesis.

Detailed Description of the Preferred Embodiments

In accordance with the present invention, a filler material for a surgically implantable prosthesis comprising a synthetic triglyceride composition is provided.
The triglyceride composition is preferably resistant to oxidation by the provision of fully saturated alkyl chains on the triglycerides and the triglyceride composition contains alkyl chains (fatty acid side chains) of varying lengths in a selected proportion such that the triglyceride composition has a viscosity of at least about 10,000cps at a temperature of between about 32°C and 40°C.

Fully saturated alkyl chains from fatty acids of 20 the desired carbon chain length are utilized in the preparation of the triglyceride filler material of this invention to reduce or eliminate the vulnerability of the triglyceride composition to oxidation which can result in the production of free radicals which reduce the 25 biocompatibility of the filler material and could have adverse effects on surrounding tissue in the event of leakage or implant rupture. While it is preferred that the alky-chains be fully saturated for these reasons, synthetic triglyceride compositions that are substantial-30 ly saturated are effective in limiting the oxidation of the composition and represent a significant improvement over naturally occurring triglycerides that are typically highly unsaturated. It is preferable if the alkyl groups are at least about 80% saturated, and more preferably 35 greater than 90% saturated. To further limit the possi-

6

bility of oxidation of a triglyceride composition, antioxidants such as tocopherol (Vitamin E) can be added to the composition.

The triglyceride composition of the present inven-5 tion can be prepared using standard methods known to those skilled in the art such as by reacting pure, fully saturated fatty acids of the desired carbon length with purified glycerol in an esterification reaction. resulting triglyceride is purified from the reaction 10 mixture by known techniques to provide a pure, non-contaminated triglyceride. Fatty acids varying in length from 4 carbons to at least 26 carbons may be advantageously used in this reaction to form a triglyceride having alkyl chains of the desired length. The reac-15 tion mixture may contain only a single fatty acid of a desired chain length or the reaction mixture may contain a mixture of fatty acids of different lengths. Preferably, saturated fatty acids of varying carbon length are provided in pre-selected proportions to yield a triglyc-20 eride composition having a selected viscosity.

Alternatively, triglycerides can be prepared with only a single carbon length fatty acid and the filler material of the present invention is obtained by blending different triglycerides, each presenting alkyl chains of a uniform chain length, in such a manner as to provide a blend of triglycerides containing a mixture of alkyl chain lengths having the selected viscosity. When this method is employed, it must be understood that the proportions of the different carbon chain lengths needed to obtain the selected viscosity, as compared to the proportions needed to obtain a composition having the same viscosity by the preferred method, are not necessarily identical because of the differences in the structure of the compositions.

In the preparation of a triglyceride composition of a selected viscosity, a composition having a known

7

proportion of alkyl chain lengths is prepared and the viscosity and tactile response of the composition in the appropriate temperature range is determined. If the resulting composition does not have the selected or desired viscosity or tactile response, the alkyl chain length proportions are varied and a new composition prepared and analyzed.

By preparing a triglyceride composition in accordance with the method of this invention, an implant con-10 taining a filler material of a desired or pre-selected viscosity can be provided by adjusting the proportions of the varying lengths of alkyl chains on the triglycerides. If a more viscous composition having a "stiffer" tactile response is desired, a higher proportion of longer carbon 15 chains and a higher average molecular weight, e.g. 10-14 carbon length fatty acids, can be used. If a less viscous composition having a more fluid tactile response is desired, a higher proportion of shorter carbon chains and having a lower average molecular weight, e.g. 6 or 8 20 carbon length fatty acids, can be used. By preparing triglyceride compositions according to the method described above using different proportions of fatty acids of varying carbon chain length, an array of triglyceride compositions having different viscosities and 25 tactile properties can be determined. This provides a consumer with a choice among implants having a range of viscosities and permits the selection of an implant containing a filler material of a selected viscosity and tactile iesponse.

It should be understood that triglyceride compositions containing saturated alkyl chains of the desired length can also be purchased commercially and blended in the selected proportions to obtain a composition of the selected viscosity.

35 The triglyceride composition of this invention preferably has a viscosity substantially greater than

that of naturally occurring triglyceride oils, such as the peanut oil and sunflower seed oil triglycerides disclosed by Destouet et al. Naturally occurring triglycerides, especially the vegetable triglycerides disclosed in 5 Destouet et al., typically have a viscosity of approximately 30cps. The filler material of the present invention preferably has a viscosity between about 10,000cps and about 50,000cps, in a temperature range of between about 32°C and about 40°C, and more preferably between 10 about 10,000cps and 20,000cps. The viscosity of a triglyceride composition of this invention is measured by conducting a standard viscosity test known to those skilled in the art, such as the rotating spindle procedure, or by the measurement of the flow of the fluid 15 compared to a known standard, the flow being inversely proportional to its viscosity. It has been found that a synthetic triglyceride composition having a viscosity in the preferred range provides a tactile response substantially the equivalent of normal human tissue, and in 20 particular, normal human breast tissue.

As described, the triglycerides used in the triglyceride composition of the present invention may contain alkyl chains varying in length from 4 carbons to 26
carbons in proportions which provide the desired viscosity. The triglycerides are of the formula

35 where R¹, R², and R³ are independently selected from alkyl chains of between 4 and 26 carbons in length. To determine whether a particular proportion of triglycerides of differing alkyl chain lengths in a triglyceride composition is sufficient for use in this invention, a desired

q

combination is prepared and its viscosity measured at around body temperature, approximately 37°C. tested composition exhibits a viscosity of about 10,000cps, it is considered suitable for use as a filler 5 material in accordance with the present invention. It is believed that by preparing a triglyceride composition · having a blend of alkyl chains of varying length in the desired proportional amounts, a coincidence of melting points of the various triglycerides is achieved which 10 results in a composition having the desired viscosity. A triglyceride composition of this invention preferably comprises a blend of at least three triglycerides containing alkyl chains of between 6 and 14 carbons in length., A particular preferred triglyceride composition 15 suitable for use in the present invention has been prepared and contains triglycerides having about 8% eight carbon saturated alkyl chains, about 8% ten carbon saturated alkyl chains, and about 84% twelve carbon saturated alkyl chains. This synthetic triglyceride composition 20 has a viscosity of about 15,000cps at 37°C, has a consistency similar to "warm butter" and closely approximates the tactile properties of a normal human breast.

In another exemplary synthetic triglyceride composition, a triglyceride composition having a viscosity

25 that provides a more "fluid" tactile response has been prepared by producing a composition having about 15% six carbon saturated alkyl chains, about 15% eight carbon saturated alkyl chains, and about 70% ten carbon saturated alkyl chains in the overall triglyceride composition.

30 This composition has a viscosity of about 10,000cps at 37°C.

In an alternate embodiment of the invention, a synthetic triglyceride composition having a lower average molecular weight as a result of reduced average fatty acid side chain length and which is a liquid at room temperature is provided which is suitable for use in

inflatable devices. This filler material is prepared from fully saturated fatty acids as previously described and provides a filler material that has a viscosity of approximately 30-100cps. This filler material, there-5 fore, has a viscosity similar to the viscosity of naturally occurring triglyceride oils, but is not as vulnerable to oxidation (as previously described). Because this embodiment is a liquid at room temperature, it can readily be injected via a small diameter delivery tube into a 10 previously implanted inflatable-type device. An exemplary synthetic triglyceride composition of this embodiment contains triglycerides having about 10% eight carbon saturated alkyl chains, about 60% ten carbon saturated alkyl chains, and about 30% twelve carbon saturated alkyl 15 chains. This filler composition has a viscosity of about 30cps, similar to naturally occurring triglyceride oils, but contains fully saturated alkyl chains and is thereby resistant to oxidation in contrast to naturally occurring triglyceride oils. The filler material previously de-20 scribed having a viscosity of about 10,000cps is a solid at room temperature which must be heated to higher than physiological temperatures (e.g. 40°C - 43°C) to liquify the filler material for introduction into an implanted inflatable device via a small tube. Thus, the first 25 embodiment of the triglyceride composition as previously described can be used with inflatable devices, but requires the introduction technique to be revised by preheating the filler material in its container to reduce its viscosity for introduction. When this method is 30 employed, care must be taken not to increase the temperature of the composition too much as damage to surrounding tissues could occur during introduction into the device.

Both embodiments of the filler material are suitable for use in implantable prostheses of the type comprising a sealable shell or envelope. Techniques for manufacturing and filling this type of prosthesis are

11

well known to those of ordinary skill in the art and may be used herein. Thin walled shells comprised of a silicone polymer as well as other known shell materials are suitable for use in combination with the filler material of this invention. As described, the shells may be of the type that are pre-filled or that may be filled after implantation through small diameter delivery tubes.

Just as prior art filler materials have been found to migrate through shells made of semi-permeable

10 membranes such as silicone polymers, the filler material of the present invention is expected to do the same.

However, with filler material of the present invention, higher molecular weight carbon chains may be employed and the larger carbon chains will minimize the amount of

15 filler material which does migrate. Health risks associated with migration of filler material are thus expected to be reduced or even eliminated.

It is to be understood that various changes and modifications which may be made to the invention as would 20 be apparent to those skilled in the art are considered to be included in the teaching of the disclosure, and it is intended that the invention be limited only by the scope of the claims appended hereto.

12

What is claimed is:

- 1. A filler material for a surgically implantable prosthesis comprising a biocompatible synthetic triglyceride.
- 2. The filler material of claim 1 wherein the synthetic triglyceride has a viscosity greater than naturally occurring triglycerides.
- 3. The filler material of claim 2 wherein the synthetic triglyceride has a viscosity providing a tactile response substantially the equivalent of the tactile response of a normal human breast.
- 4. The filler material of claim 1 wherein the synthetic triglyceride is resistant to oxidation.
- 5. The filler material of claim 4 wherein the synthetic triglyceride contains saturated alkyl groups.
- 6. The filler material of claim 1 wherein the filler material is a liquid at about 23°C.
- 7. A breast implant containing a biocompatible filler material having a viscosity providing a tactile response substantially the equivalent of the tactile response of a normal human breast.
- 8. The breast implant of claim 7 wherein the biocompatible filler material is a synthetic triglyceride.
- 9. The breast implant of claim 7 wherein the filler material is radiolucent under standard mammographic procedures, intensities and exposure times.

WO 95/25549

PCT/US94/12394

10. The breast implant of claim 7 wherein the filler material is resistant to oxidation.

13

- 11. The breast implant of claim 8 wherein the synthetic triglyceride contains saturated alkyl groups.
- 12. A surgically implantable prosthesis containing a filler material, said filler material being capable of being provided in a range of viscosities thereby permitting the prosthesis to have a pre-selected viscosity.
- 13. The surgically implantable prosthesis of claim 12 wherein the filler material is provided at a viscosity providing a tactile response substantially the equivalent of the tactile response of a normal human breast.
- 14. The surgically implantable prosthesis of claim 13 wherein the filler material is biocompatible.
- 15. The surgically implantable prosthesis of claim 14 wherein the filler material is a synthetic triglyceride.
- 16. The surgically implantable prosthesis of claim 15 wherein the filler material is resistant to oxidation.
- 17. The surgically implantable prosthesis of claim 12 wherein the filler material is a liquid at about 23°C.
- 18. A method for preparing a synthetic triglyceride filler material of a pre-selected viscosity for use in a surgically implantable prosthesis, the method comprising:
- selecting a viscosity for the synthetic triglyceride filler material; and

formulating a synthetic triglyceride filler material composition having synthetic triglycerides comprised of alkyl chains of varying length in proportional amounts WO 95/25549

PCT/US94/12394

sufficient to yield a filler material of the selected viscosity.

- 19. The method of claim 18 wherein the synthetic triglyceride filler material is formulated by reacting proportional amounts of fatty acids of different chain lengths with glycerol in an esterification reaction to yield the synthetic triglyceride filler material of the pre-selected viscosity.
 - 20. The method of claim 18 wherein the synthetic triglyceride filler material composition is formulated by obtaining synthetic triglycerides of different alkyl chain length and mixing said triglycerides together in proportional amounts to yield the synthetic triglyceride filler material of the pre-selected viscosity.
 - 21. The method of claim 19 wherein the viscosity selected provides a tactile response substantially the equivalent of the tactile response of a normal human breast.
 - 22. The method of claim 21 wherein the fatty acids are between 4 and 26 carbons in length.
 - 23. The method of claim 22 wherein three fatty acids of between 6 and 14 carbons in length are selected and provided in proportional amounts to yield a filler material having a viscosity of at least about 10,000cps when reacted with glycerol.
 - 24. The method of claim 20 wherein the viscosity selected provides a tactile response substantially the equivalent of the tactile response of a normal human breast.

15

- 25. The method of claim 24 wherein the fatty acids are between 4 and 26 carbons in length.
- 26. The method of claim 25 wherein three fatty acids of between 6 and 14 carbons in length are selected and provided in proportional amounts to yield a filler material having a viscosity of at least about 10,000cps when reacted with glycerol.
- 27. A breast implant comprised of a filler material within a flexible envelope, the filler material being a synthetic triglyceride having a viscosity providing the tactile response substantially the equivalent of the 5 tactile response of a normal human breast.
 - 28. The breast implant of claim 27 wherein the filler material is resistant to oxidation.
 - 29. The breast implant of claim 27 wherein the synthetic triglyceride contains saturated alkyl groups.
 - 30. The breast implant of claim 27 wherein the filler material is radiolucent under standard mammographic procedures, intensities and exposure times.
 - 31. The breast implant of claim 27 wherein the envelope is made of silicone.
 - 32. A pethod of preparing a surgically implantable prosthesis having a pre-selected viscosity comprising:

utilizing a filler material that can be provided in a range of viscosities; and

formulating said filler material to the pre-selected viscosity.

16

- 33. The method of claim 32 wherein said filler material is a synthetic triglyceride.
- 34. The method of claim 33 wherein said synthetic triglyceride is resistant to oxidation.
- 35. The method of claim 34 wherein said synthetic triglyceride is formulated by reacting proportional amounts of fatty acids of different chain lengths with glycerol in an esterification reaction to yield the synthetic triglyceride filler material of the pre-selected viscosity.
 - 36. The method of claim 34 wherein said synthetic triglyceride is formulated by obtaining synthetic triglycerides of different alkyl chain length and mixing said triglycerides together in proportional amounts to yield the synthetic triglyceride filler material of the pre-selected viscosity.

INTERNATIONAL SEARCH REPORT

Inter: 1al Application No
PCT/US 94/12394

A. CLASS IPC 6	sification of subject matter A61L27/00 A61F2/12		
According	to International Patent Classification (IPC) or to both national class	ssification and IPC	
B. FIELD	S SEARCHED		
	documentation searched (classification system followed by classific A61L A61F	ation symbols)	
	ation searched other than minimum documentation to the extent tha		
Electronic	data base consulted during the international search (name of data b	ase and, where practical, search terms used;	
C. DOCU	MENTS CONSIDERED TO BE RELEVANT	_	
Category *	Citation of document, with indication, where appropriate, of the	relevant passages	Relevant to claim No.
x	US,A,4 995 882 (DESTOUET J.M.) 2 1991 cited in the application	26 February	1
	see abstract; claim 6		
X	WO,A,93 20780 (THE TRUSTEES OF T UNIVERSITY OF PENNSYLVANIA) 28 0 1993		12-14
	see page 5, line 7 - line 8 see page 11, line 32 - line 37;	claim 32	
A	WO,A,94 04095 (LIPOMATRIX) 3 Mar see claim 1	rch 1994	1
P,A	WO,A,94 16647 (HANG-FU L.) 4 Aug see claim 1	ust 1994	1
Furt	her documents are listed in the continuation of box C.	X Patent family members are listed	in annex.
* Special ca	tegories of cited documents:	"T" later document published after the int	ernational filing date
"A" document defining the g veral state of the art which is not cited to understand the principle or to considered to be of parous relevance on the considered to be of parous relevance."		th the application but	
"E" earlier document but published on or after the international "X" document of particular relevance		"X" document of particular relevance; the cannot be considered novel or cannot	
"L' document which may throw doubts on priority claim(s) or involve an inventive step when the do which is cited to establish the publication date of another "Y" document of particular relevance: the		cument is taken alone daimed invention	
O docum	n or other special reason (as specified) ent referring to an oral disclosure, use, exhibition or means	cannot be considered to involve an in document is combined with one or m	ventive step when the ore other such docu-
other means ments, such combination being obvior in the art. "P" document published prior to the international filing date but later than the priority date claimed "&" document member of the same patent			
	actual completion of the international search	Date of mailing of the international se	
1	0 August 1995	1 8. 08. 95	
Name and r	nailing address of the ISA European Patent Office, P.B. 5818 Patentiaan 2	Authorized officer	
	NL - 2280 HV Ripwijk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+ 31-70) 340-3016	Peltre, C	

INTERNATIONAL SEARCH REPORT

information on patent family members

Inten tal Application No
PCT/US 94/12394

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
US-A-4995882	26-02-91	CA-A-	1328544	19-04-94
WO-A-9320780	28-10-93	US-A- AU-B-	5391203 4102793	21-02-95 18-11-93
WO-A-9404095	03-03-94	AU-B- EP-A-	5083593 0656768	15-03-94 14-06-95
WO-A-9416647	04-08-94	AU-B- CA-A- EP-A-	6030994 2132216 0636015	15-08-94 04-08-94 01-02-95